

# UltraRack®

IT Server Racks



**SR series - 800W Heavy-duty Rack**



Flexible, easy to install and energy efficient, the **UltraRack®** heavy-duty rack and options let you address your IT needs quickly. The new UltraRack SR series combines next-generation structural integrity, cooling, power distribution, cable management, security, ease-of-use capabilities, and a wide choice of configuration options for increased flexibility.

The **UltraRack®** heavy-duty racks integrates seamlessly with all Austin Hughes infrastructure equipment, including InfraAisle Containment, InfraPower PDUs, InfraCool Fan Units, InfraSolution SmartCard handles, CyberView KVM and LCD drawers.

In addition, we have made important structural enhancements from the previous version of racks. Enhancement has been made to help providing that your mounted devices are easy to access and receive more effective airflow. **UltraRack®** SR series 800W racks address specific market requirements for additional space for power and cable management.

**RoHS2**  
COMPLIANCE

**REACH**

**Green Production**

The SR series rack is recognized as RoHS2 and REACH compliance by SGS accredited testing laboratory.

**ISO-Certified**

**9001 14001**

The design and manufacturing process of the series achieves the BSi ISO9001 quality control plus ISO14001 environment standard.

**1500 kg**

**3300 lb**

Designed for heavy-duty application, the SR series rack has passed the loading test.

## Key Highlights

- Heavy-duty framework supports up to 1500 kg load capacity
- 800mm wide and provides sufficient space for managing your data and power cables
- Perforated rack doors ensure ideal airflow direction
- Well-engineered to accommodate tool-less mounting PDU x 4
- Framework allows multi-dimensional cable pathways and numerous efficient cabling options
- Easy to deploy and adaptable to Aisle containment to achieve an efficient airflow management
- Quick release mechanism design for door and split side panel
- Tool-less adjustment for front and rear 19" rails
- Up to 500 individual key locks upgrade available
- Universal-fit platform for multiple brands of servers and 19" rackmount equipment



## Total Rack Solution

Our new design, comprehensive valued options and extensive product range offer complete solutions for SR series rack.

### >>> Cabling

- Framework allows multi-dimensional cable pathways
- Numerous efficient cabling options

### >>> AirFlow

- Air Blanking Panels prevent air recirculation by occupying unused rack space
- Rack Seal Kits prevent air loss underneath the racks and the gap between racks

### >>> Cooling

- EXD Door removes heated air and prevents the build up of heated air inside the rack
- InfraCool Fan Unit provides variety fan unit form factors for different cooling requirement

### >>> Power

- Metered PDU for cost efficient power distribution
- Intelligent kWh PDU for remote management

### >>> Security

- Standalone smartcard handles with an affordable price and easy installation
- Networked version enables complete smartcard rack access management with software

### >>> Control

- LCD console drawer combines the display, keyboard and touchpad in 1U rack space
- KVM allows remote or local access and control to multiple servers in the rack

## Standard Package / Size

	Model No.	Width		Depth				Height			
				Overall ( door to door )		Effective ( frame to frame )		Overall ( w/ casters )		Effective	
		mm	inch	mm	inch	mm	inch	mm	inch	mm	inch
42U	SR-8942	800	31"	972	38"	900	35"	2035	80"	1867	74"
	SR-8042	800	31"	1072	42"	1000	39"	2035	80"	1867	74"
	SR-8242	800	31"	1200	47"	1128	44"	2035	80"	1867	74"
45U	SR-8945	800	31"	972	38"	900	35"	2168	85"	2000	79"
	SR-8045	800	31"	1072	42"	1000	39"	2168	85"	2000	79"
	SR-8245	800	31"	1200	47"	1128	44"	2168	85"	2000	79"
47U	SR-8947	800	31"	972	38"	900	35"	2257	89"	2089	82"
	SR-8047	800	31"	1072	42"	1000	39"	2257	89"	2089	82"
	SR-8247	800	31"	1200	47"	1128	44"	2257	89"	2089	82"
52U	SR-8252	800	31"	1200	47"	1128	44"	2480	98"	2312	91"

\*\*Custom size on request



REACH

Standard Package	Configuration	Baying Package
	Static Loading: 1500 kg / 3300 lb	
✓	Color Option: Black or Grey White	✓
✓	Enhanced Framework w/ Cable Management Feature	✓
✓	Fully Vented Top Cover w/ Cable Access Channel	✓
✓	19" Rails w/ Unit Mark, Front & Rear Pairs	✓
✓	Front Perforated Door w/ 3-pt Handle Lock	✓
✓	Rear Perforated Middle Split Door w/ 3-pt Handle Lock	✓
✓	Split Side Panel w/ Lock & Latch, Pair	✗
✓	Heavy Duty Caster & Adjustable Feet, set of 4	✓
✓	Dynamic Earthing Kit	✓
✓	M6 Screw Fixing, Pack of 50	✓

## Standard Color



- Black ( RAL 9005 )
- Grey White ( RAL 9002 )

\*\* Custom color on request




## Fully Perforated Door

- Door ventilation up to 80% perforated area
- Stylish hexagon pattern



Unit : mm



Standard Package

Standard Split

Quick access design for service from side panel

Fully Perforated

Perforated w/ 3-point handle lock

Perforated Top

Fully Perforated Middle Split

Space-saving design for narrow aisle w/ 3-point handle lock

Front / Rear Door

Glass

Toughened and safe glass w/ single-point handle lock

Steel Vented

Ventilated infill area w/ single-point handle lock

Fully Perforated 2 Co-location

Glass or steel door available w/ single-point handle lock  
\*\* Individual key lock option

Fully Perforated 4 Co-location

Glass or steel door available w/ single-point handle lock  
\*\* Individual key lock option

Side Panel

Fully Perforated Split

Allows heat exhaust from high density equipment

Top Cover

Plain Top

Ideal for air-blanked racks

Fan Top

The ventilation design enhances cooling capabilities by top fan tray



Austin Hughes responded with a comprehensive selection of components for ideal cable management

## ■ Top Cable Entry with Brush front & rear end

- Cable entry size : 55 x 500 mm
- Top brushed cover prevents undesirable dust and hot air recirculation

Part no. : TCB-2E

## ■ Side Partition with Cable Brush, pc

- Ideal for bayed racks
- Cable entry size : 110 x 500 mm
- Allow cable passage to adjacent racks
- Hole contains brushes to control airflow

Part no. : BVP-4210-SR / 4212-SR  
BVP-4510-SR / 4512-SR  
BVP-4710-SR / 4712-SR

## ■ Top Cable Entry with Brush left & right side

- Cable entry size : 110 x 500 mm
- Top brushed cover prevents undesirable dust and hot air recirculation

Part no. : TCB-2S

## ■ Full Height Cable Brush left & right side

- Brush width : 100 mm
- Provide proper airflow within the rack while allowing cables to pass through

Part no. : VCB-42U  
VCB-45U  
VCB-47U

## ■ Cable Cover Panel, pair

Part no. : VCP-42U ( 42U )  
VCP-45U ( 45U )  
VCP-47U ( 47U )

## ■ Cable Ring, pack of 10

- Size : 88 x 180 mm ( front )  
88 x 120 mm ( rear )
- Steel & Rigid structure

Part no. : CMR-180P ( front )  
CMR-120P ( rear )

## ■ Full Height Cable Tray, pair

- Width : 150 mm

Part no. : CT-42U-W150 ( 42U )  
CT-45U-W150 ( 45U )  
CT-47U-W150 ( 47U )

## ■ Cable Management Panel, pc

- Handle big amount of cabling

Part no. : CMP-1B ( 1U )  
CMP-2B ( 2U )

## ■ Finger Guide, set of 2 sides

- Provide an organized cable system
- Material : Plastic
- Depth : 105 mm

Part no. : FG-40U ( 42U )  
FG-45U ( 45U / 47U )

## ■ Ring Cable Manager, pair

- Size : 120 x 1023 x 100 mm
- 120mm cable ring x 4
- Material : Steel
- Positioned on the rear

Part no. : RCM-120

## ■ Ring Cable Manager, pair

- Size : 180 x 1023 x 100 mm
- 180mm cable ring x 4
- Material : Steel
- Positioned on the front

Part no. : RCM-180

## ■ Fibre Management Panel, pc

- Maintain a neat & organized cable layout

Part no. : FMP-2B ( 2U )  
FMP-3B ( 3U )  
FMP-4B ( 4U )

## ■ Fibre Management Channel, pair

- Material : Steel / Plastic
- Positioned on the front or rear

Part no. : FMC-42U  
FMC-45U  
FMC-47U

Based on measurements at multiple data centers, more than 50% of valuable conditioned air cannot reach the air intake of IT equipment due to unsealed openings. Hence, the aisle containment associated with an extensive range of sealing components is essential for IT equipment reliability.


The **InfraAisle** Containment with UltraRack racks are designed to enhanced thermal management in data center by creating a one-way path for airflow that eliminates the mixing of hot and cold air. An ideal data center environment is given with the use of Air Blanking Panels and Seal Kits in the aisle containment and server racks.



## Full Height Air Blanking Panel Front left & right side

- Used to fill in open spaces on racks to maintain a proper airflow
- Reduce the hot air recycling from active equipment into cold aisle
- Made of steel for strength and durability
- Black or Grey white color

Part no. : **ABP-V42U-SR**  
**ABP-V45U-SR**  
**ABP-V47U-SR**



## Tool-less Air Blanking Panel, pc

- Quick snap-in and release by turning fasteners
- EIA-310-D compliant for 19" equipment
- Rounded design eliminates sharp corners
- Plastic for enhanced aesthetics & light weight
- Steel for strength & 1 ~ 8U height selection
- Plastic Panel : Height - 1U  
Color - Dark
- Steel Panel : Height - 1U / 2U / 3U / 4U / 5U / 6U / 7U / 8U  
Color - Black or Grey white

Part no. :  
**ABP-1P** ( Plastic )  
**ABP-1 / 2 / 3 / 4 / 5 / 6 / 7 / 8** ( Steel )

## Bay Seal Kit, pc


- Seal spacing between two bayed racks without side panels
- Eliminate bypass air from front to rear
- Designed for front only

Part no. : **SSK-42U**  
**SSK-45U**  
**SSK-47U**

## Front Bottom Seal Kit, pc

- Seal spacing between the floor and rack base
- Eliminate bypass air
- Designed for front only

Part no. : **BSK-SR**




## Rack to Floor Seal Kit, set of 2

- Seal spacing between the floor and rack base
- Eliminate bypass air
- Only available for rack with casters
- Front and rear seal kit for each bayed rack
- Left and right side seal kit for the row end racks

Part no. :  
**PSK-800W-SR** ( front & rear )  
**PSK-1000D-SR** ( left & right )  
**PSK-1200D-SR** ( left & right )

The biggest challenge in today's data center is thermal management, which is no surprise considering the average heat load generated per equipment rack has double in this century. Cooling the equipment in an enclosed rack has always been important.

Austin Hughes has been incorporating ventilation and cooling requirement. We can incorporate top rackmount or door mount fan units, rear extract fan door and intelligent fan models depending on your application.



## Extract Fan Door


- Remove heated air and prevent build-up of heated air inside the rack, which can cause equipment to overheat and shut down
- Provide a total of 1080 CFM peak exhaust airflow
- Front temp. LED w/ bundled temp. sensor x 1
- Fan ON / OFF by door switch for safety
- w/ 3-point handle lock
- Black or Grey white color

Part no. ( full width door ) :

EXD-42.8-VH  
EXD-45.8-VH  
EXD-47.8-VH

Part no. ( middle split door ) :

EXDS-42.8-VH  
EXDS-45.8-VH  
EXDS-47.8-VH



## 33U Door Mount Extract Fan Panel

- Improve heat extraction from high density racks
- Front temp. LED w/ bundled temp. sensor x 1
- Easy installation with common tools
- Slim and light weight design at 3.9 kg / 8.6 lb only
- Designed for low noise and high airflow performance
- 9 fans ( 972 CFM )

Intelligent ( Master ) : MRF-33.9A

Intelligent ( Slave ) : RF-33.9A

Basic : F-33.9A

## 1U Fan Tray

- Exhaust hot air out of rack through top level rackmount
- Avoid equipment hot spots in rack by middle level rackmount
- Intake cool air in a rack by bottom level rackmount
- Front temp. LED w/ bundled temp. sensor x 1
- Provide low noise and high airflow performance
- 9 fans ( 972 CFM ) / 6 fans ( 648 CFM ) / 3 fans ( 324 CFM )

Intelligent ( Master ) : MRF-1.3 / MRF-1.6 / MRF-1.9

Intelligent ( Slave ) : RF-1.3 / RF-1.6 / RF-1.9

Basic : F-1.3 / F-1.6 / F-1.9


## 33U Door Mount Intake Fan Panel

- Intake air from cold aisle into the rack
- Front temp. LED w/ bundled temp. sensor x 1
- Easy installation with common tools
- Slim and light weight design at 3.9 kg / 8.6 lb only
- Designed for low noise and high airflow performance
- 9 fans ( 972 CFM )

Intelligent ( Master ) : MRF-33.9B

Intelligent ( Slave ) : RF-33.9B

Basic : F-33.9B



## Raised Floor Mount Fan Unit

- Intake underfloor cold air into the aisle and rack
- Eliminate hot spots by proper airflow distribution
- Temp. LED w/ bundled temp. sensor x 2
- Individual fan switch x 4 for power and CFM control
- Easy installation without rack movement
- Designed for high airflow performance
- 4 fans ( 2172 CFM )

Intelligent : WF-66.4


Basic : F-66.4

With today's increasing demand for power management solution, a complete suite of rack PDU models is required specifically to help data center IT managers meet their rapidly escalating power requirements.

**InfraPower®** provides a complete power management solution from Basic, Metered, Intelligent kWh, to Outlet Level intelligent kWh models. Our PDUs are also offered in many sizes and configurations depending on voltage, current, number and type of connections.


[Details](#)

cUL certified for specific configurations



InfraPower® 1-Phase PDU Family	Monitored		Switched		Metered	-
	W	Wi	WS	WSi	MD	Basic
Outlet AMP - kWh Measurement		✓		✓		
Outlet Switch ON / OFF			✓	✓		
Hot-Swap Meter	✓	✓	✓	✓		
1.8" Color LCD	✓	✓	✓	✓		
Circuit Amp - kWh Measurement	✓	✓	✓	✓		
Temp-Humid Sensor port x 2	✓	✓	✓	✓		
16 PDU Levels in Single Daisy Chain	✓	✓	✓	✓		
One IP Access up to 16 PDU Levels	✓	✓	✓	✓		
SNMP Capability v2 / v3	✓	✓	✓	✓		
Free Management Software	✓	✓	✓	✓		
Lockable IEC Outlet Model	✓	✓	✓	✓	✓	✓
Individually Fused Outlet Model	✓	✓	✓	✓	✓	✓
63A Model ( only for 230V PDU )	✓	✓	✓	✓		✓
Local Meter	✓	✓	✓	✓	✓	
Tool-less Mounting for Vertical PDU	✓	✓	✓	✓	✓	✓
0U / 1U / 2U Form Factors	✓	✓	✓	✓	✓	✓
Voltage 230V / 208V / 110V	✓	✓	✓	✓	✓	✓
Hydraulic Magnetic Circuit Breaker	✓	✓	✓	✓	✓	✓
Operating Temperature Range -5°C to 60°C	✓	✓	✓	✓	✓	✓
Outlet Types : IEC C13	✓	✓	✓	✓	✓	✓
IEC C19	✓	✓	✓	✓	✓	✓
IEC C13 + C19	✓	✓	✓	✓	✓	✓
IEC Lockable	✓	✓	✓	✓	✓	✓
IEC Individually Fused	✓	✓	✓	✓	✓	✓
NEMA	✓	✓	✓	✓	✓	✓
UK / UK + IEC	✓	✓	✓	✓	✓	✓
SCH / SCH + IEC	✓	✓	✓	✓	✓	✓

Colored PDU & Power Cords



Rackmount PDU





Rack level access security has become critically important for all data centers and server rooms. More and more IT managers have recognized this need and are upgrading their racks with smartcard access control. To meet the increasing needs, Austin Hughes offers the **InfraSolution®** - Integrated IT Access Control & Monitoring for Data Center.

Two InfraSolution versions for data center rack are provided :

**InfraSolution® S** Rack Smartcard Access - Standalone

[Details](#)


**InfraSolution® X** Rack Smartcard Access - Networked

[Details](#)



Comparison Table		InfraSolution® S Standalone	InfraSolution® X Networked
Key Hardware	Smartcard Handle	✓	✓
	Door Sensor	Optional	✓
	1U Control Box		✓
Compatibility	Proximity Smartcard	✓	✓
	MiFARE Smartcard	✓	✓
	SNMP for Client's BMS		✓
Handle Releasing	By Smartcard	✓	✓
	By Dual Card Authentication	✓	
	By Software Remote		✓
	By Mechanical Key	✓	✓
Software Features	Smartcard Authentication	✓	✓
	Smartcard / De-authentication	✓	✓
	Remote Handle Unlocking		✓
	Remote Monitoring		✓
	E-mail alarm		✓
	Detail Log for Reporting		✓
Integrated PDU	kWh Switched		✓
	kWh Monitored		✓
	Outlet kWh Switched		✓
Integrated Fan	Remote 33U Fan Panel		✓
	Remote 1U Fan Tray		✓
Environmental Sensors	Temp. + Humid.		✓
	Temp.		✓
	Smoke		✓
	Shock		✓
	Water		✓
	Flashing LED Beacon		✓
	LED light bar		✓

Proximity & MiFARE Compatible



LED for Clear Lock Status Indication



Austin Hughes solutions provide data center managers and administrators instant secure, local and remote access control to mission critical equipment. Our leading edge **CyberView™** LCD console drawer and KVM Solutions provide the widest range, available on the shortest lead-times in the market today whilst ensuring capital equipment and software management costs are kept to an absolute minimum.



## LCD Console Drawer

[Details](#)

CyberView LCD console drawers completely fulfill customers' needs emerged in today's market sector via different series such as "F" 1080p, "W" widescreen and "RKP" enhanced version. 1U Dual Slide drawer, SUN and MAC solutions available



CyberView™ LCD Console Drawer	F117	W119	RKP117 / 119	D117 / 119
Panel Size	17"	19"	17" / 19"	17" / 19"
U Height	1U	1U	1U	1U ( Dual Slide )
Resolution	Full HD 1080p	1440 x 900	1280 x 1024	1280 x 1024
Brightness	300 cd/m2	300 cd/m2	250 cd/m2	250 cd/m2
VGA	✓	✓	✓	✓
DVI	✓	✓	option	option
HDMI	option	option	option	option
Audio	option	option	option	option
KVM Integration	✓	✓	✓	✓
IP Access	option	option	option	option

## Rackmount KVM

[Details](#)

Austin Hughes has expanded its range of KVM solutions. Including the new USB Hub KVM and DVI-D KVM, there are various KVM series suitable for different customer requirements. Besides, we offer KVM extender for KVM usage enhancement in existing customer environment.

Cat6 KVM



DB-15 KVM



DVI-D KVM



USB Hub KVM



CyberView™ KVM Family	Matrix Cat6 KVM	Combo Cat6 KVM	Matrix DB-15 KVM	Combo DB-15 KVM	DVI-D KVM	USB Hub KVM
KVM Port					DVI + USB	
Port #	32 / 16	32 / 16 / 8	16 / 8	16 / 8	12	16 / 8
1920 x 1080 Support	✓	✓	✓	✓	✓	✓
1920 x 1200 Support			✓	✓	✓	✓
Server-side KB / MS	USB / PS2	USB / PS2	USB / PS2	USB / PS2	USB	USB
Server-side Video	VGA / DVI	VGA / DVI	VGA	VGA	DVI-D	VGA
Server-side Audio					Stereo	
USB Device Port						2 x USB2.0
Max. Distance ( to Server )	40M	40M	4.5M	4.5M	4.5M	4.5M
Cascade Level	8	8	8	8		
On-Screen Menu	✓	✓	✓	✓		✓
Simultaneous Users ( max. 4 )	✓		✓			
IP Access Option	✓	✓	✓	✓		✓
Multi-user Profile	✓	✓	✓	✓		✓
1U Standalone KVM	✓	✓	✓	✓	✓	✓
KVM Rear Kit for LCD Console Drawer	✓	✓	✓	✓	✓	✓

## Cabling

<b>CMP-1B</b>	1U cable management panel
<b>CMP-2B</b>	2U cable management panel
<b>CMR-180P</b>	Cable Ring on the front, 88 x 180 mm, pack of 10
<b>CMR-120P</b>	Cable Ring on the rear, 88 x 120 mm, pack of 10
<b>FG-40U</b>	Finger guide for 42U rack, set of 2 sides
<b>FG-45U</b>	Finger guide for 45U / 47U rack, set of 2 sides
<b>VCB-42U</b>	42U full height cable brush, left & right side
<b>VCB-45U</b>	45U full height cable brush, left & right side
<b>VCB-47U</b>	47U full height cable brush, left & right side
<b>VCP-42U</b>	42U cable cover panel, pair
<b>VCP-45U</b>	45U cable cover panel, pair
<b>VCP-47U</b>	47U cable cover panel, pair
<b>CT-42U-W150</b>	42U full height cable tray, set of 2 sides, 150 mm wide
<b>CT-45U-W150</b>	45U full height cable tray, set of 2 sides, 150 mm wide
<b>CT-47U-W150</b>	47U full height cable tray, set of 2 sides, 150 mm wide
<b>RCM-180</b>	Ring cable manager on the front, 180 x 1023 x 100 mm, pair
<b>RCM-120</b>	Ring cable manager on the rear, 120 x 1023 x 100 mm, pair
<b>TCB-2E</b>	Top cable entry w/ brush, front & rear end
<b>TCB-2S</b>	Top cable entry w/ brush, left & right side
<b>FMP-2B</b>	2U fibre management panel
<b>FMP-3B</b>	3U fibre management panel
<b>FMP-4B</b>	4U fibre management panel
<b>FMC-42U</b>	42U vertical fibre management channel, pair
<b>FMC-45U</b>	45U vertical fibre management channel, pair
<b>FMC-47U</b>	47U vertical fibre management channel, pair
<b>BVP-4210-SR</b>	Side partition w/ cable brush, for SR 42U 1000D rack
<b>BVP-4212-SR</b>	Side partition w/ cable brush, for SR 42U 1200D rack
<b>BVP-4510-SR</b>	Side partition w/ cable brush, for SR 45U 1000D rack
<b>BVP-4512-SR</b>	Side partition w/ cable brush, for SR 45U 1200D rack
<b>BVP-4710-SR</b>	Side partition w/ cable brush, for SR 47U 1000D rack
<b>BVP-4712-SR</b>	Side partition w/ cable brush, for SR 47U 1200D rack

## Cooling Fan Unit - Basic Model

<b>TF-02</b>	Basic top fan tray, 2 fans
<b>TF-04</b>	Basic top fan tray, 4 fans
<b>TF-06</b>	Basic top fan tray, 6 fans
<b>F-1.3 / 1.6 / 1.9</b>	Basic 1U fan tray, 3 / 6 / 9 fans
<b>F-33.9A</b>	Basic 33U door mount extract fan panel, 9 fans, for rear door
<b>F-33.9B</b>	Basic 33U door mount intake fan panel, 9 fans, for front door
<b>F-66.4</b>	Basic raised floor mount fan unit, 4 fans

## Cooling Fan Unit - Intelligent Model

<b>MRF-1.3 / 1.6 / 1.9</b>	Intelligent ( Master ) 1U fan tray, 3 / 6 / 9 fans
<b>RF-1.3 / 1.6 / 1.9</b>	Intelligent ( Slave ) 1U fan tray, 3 / 6 / 9 fans
<b>MRF-33.9A</b>	Intelligent (Master) 33U door mount extract fan panel, 9 fans
<b>RF-33.9A</b>	Intelligent (Slave ) 33U door mount extract fan panel, 9 fans
<b>WF-66.4</b>	Intelligent raised floor mount fan unit, 4 fans

## Extract Fan Door

<b>EXD-42.8-VH</b>	42U x 800mm wide full width extract fan door, w/ 10 fans
<b>EXD-45.8-VH</b>	45U x 800mm wide full width extract fan door, w/ 10 fans
<b>EXD-47.8-VH</b>	47U x 800mm wide full width extract fan door, w/ 10 fans
<b>EXDS-42.8-VH</b>	42U x 800mm wide middle split extract fan door, w/ 10 fans
<b>EXDS-45.8-VH</b>	45U x 800mm wide middle split extract fan door, w/ 10 fans
<b>EXDS-47.8-VH</b>	47U x 800mm wide middle split extract fan door, w/ 10 fans

## Air Blanking

<b>ABP-1P</b>	1U tool-less air blanking panel, plastic
<b>ABP-1</b>	1U tool-less air blanking panel
<b>ABP-2</b>	2U tool-less air blanking panel
<b>ABP-3</b>	3U tool-less air blanking panel
<b>ABP-4</b>	4U tool-less air blanking panel
<b>ABP-5</b>	5U tool-less air blanking panel
<b>ABP-6</b>	6U tool-less air blanking panel
<b>ABP-7</b>	7U tool-less air blanking panel
<b>ABP-8</b>	8U tool-less air blanking panel
<b>ABP-V42U-SR</b>	42U full height air blanking panel, front left & right side
<b>ABP-V45U-SR</b>	45U full height air blanking panel, front left & right side
<b>ABP-V47U-SR</b>	47U full height air blanking panel, front left & right side
<b>BSK-SR</b>	Front bottom seal kit
<b>SSK-42U</b>	42U bay seal kit, for bayed SR rack
<b>SSK-45U</b>	45U bay seal kit, for bayed SR rack
<b>SSK-47U</b>	47U bay seal kit, for bayed SR rack
<b>PSK-800W-SR</b>	800 mm wide rack to floor seal kit, front & rear side
<b>PSK-1000D-SR</b>	1000 mm deep rack to floor seal kit, left & right side
<b>PSK-1200D-SR</b>	1200 mm deep rack to floor seal kit, left & right side

## Shelf, 19" mounting

<b>S37</b>	Fixed shelf, 370 mm deep, 50 kg loading
<b>S44</b>	Fixed shelf, 440 mm deep, 50 kg loading
<b>S58</b>	Fixed shelf, 580 mm deep, 50 kg loading
<b>S70</b>	Fixed shelf, 700 mm deep, 50 kg loading
<b>HS44</b>	Heavy duty fixed shelf, 440 mm deep, 100 kg loading
<b>HS58</b>	Heavy duty fixed shelf, 580 mm deep, 100 kg loading
<b>HS70</b>	Heavy duty fixed shelf, 700 mm deep, 100 kg loading
<b>HS80</b>	Heavy duty fixed shelf, 800 mm deep, 100 kg loading
<b>TS44</b>	Sliding shelf, 440 mm deep, 30 kg loading
<b>TS58</b>	Sliding shelf, 580 mm deep, 30 kg loading
<b>HTS70</b>	Heavy duty sliding shelf, 700 mm deep, 100 kg loading
<b>MS19</b>	Cantilever shelf, 190 mm deep, 20 kg loading
<b>MS40</b>	Cantilever shelf, 400 mm deep, 20 kg loading

## Drawer

<b>TSD-2U</b>	2U lockable drawer, 580 mm deep, 30 kg loading
<b>TSD-4U</b>	4U lockable drawer, 580 mm deep, 30 kg loading
<b>RK-1e / b</b>	1U notebook type keyboard drawer with KVM options
<b>RK-2e / b</b>	1U short depth, notebook type keyboard drawer

## Others

<b>BK-M10</b>	Top baying bracket x 2, for SR rack
<b>SR-BK</b>	Side baying screw set x 4, for SR rack
<b>M6</b>	M6 screw set, pack of 50
<b>GK</b>	Grounding kit, set of 4
<b>CLB-SD-IR-101</b>	Rack LED light bar w/ IR sensor x 1
<b>CLB-SD-IR-102</b>	Rack LED light bar w/ IR sensor x 2
<b>CuB-ET10</b>	Insulated Earth Terminal ( MOQ : pack of 5 )
<b>CuB-42U</b>	42U copper bus grounding bar, pc, w/ insulator x 3
<b>CuB-45U</b>	45U copper bus grounding bar, pc, w/ insulator x 3
<b>CuB-47U</b>	47U copper bus grounding bar, pc, w/ insulator x 3



REACH

Founded in 1995, **Austin Hughes Electronics Ltd** is a design and manufacturing group that offers a broad range of solutions based around 19 inch rack mount technology. These solutions include InfraSolution remote access control and locking, InfraPower intelligent remote management power solutions, CyberView LCD Keyboard and KVM drawers, InfraCool intelligent remote cooling system, UltraRack IT server racks & InfraAisle cold aisle containment.

**Austin Hughes** has ISO14001 and ISO9001 approved design, manufacturing, assembly and test facilities in Hong Kong and China. Austin Hughes supports a worldwide customer base, through its global locations in the Americas, EMEA and APAC and through its extensive authorized channel partner support network.

#### **APAC**

**Austin Hughes Electronics Ltd.**

Unit 3608-12, Cable TV Tower  
9 Hoi Shing Road, Tsuen Wan  
Hong Kong

**Email:** inquiry@austin-hughes.com

#### **China**

**Austin Hughes Electronics (China) Ltd.**

Hexi Road No.2, Jinxia Industrial Area  
Changan Town, Dongguan City  
Guangdong Province 523850  
China

#### **Americas**

**Austin Hughes Solutions Inc.**

41320 Boyce Road, Fremont  
CA 94538  
USA

**Email:** inquiry@austin-hughes.com

#### **EMEA**

**Austin Hughes Europe Ltd.**

Unit 1, Chancery Gate Business Centre  
Manor House Avenue  
Southampton, SO15 0AE  
United Kingdom

**Email:** info@austin-hughes.eu



**Austin Hughes** has an extensive distribution network,  
including the Americas, EMEA and APAC.  
Contact your nearest sales office for details of local representation

**[www.austin-hughes.com.hk](http://www.austin-hughes.com.hk)**

Please ask for details of other products from Austin Hughes. Every effort has been made to ensure that the information contained herein is correct. There is a possibility that the image(s) shown may not be exactly the same as the final product. The company reserves the right to modify product specifications without prior notice and assumes no responsibility for any error which may appear in this publication.

All brand names, logo and registered trademarks are properties of their respective owners.

Copyright 2018 Austin Hughes Electronics Ltd. All rights reserved.

**Distributed by:**

**Distributor by country on application**

CA-UR-551-SR800W-Q219V1